

C/. Esqueis, 25 - Pol. Ind. Can Barri 08415 Bigues (Barcelona) - Spain Tel: +34 93 865 68 28 Fax: +34 93 865 89 26 info@it3sa.com · www.it3sa.com

TECHNICAL DATA SHEET NEUTRAL LUBRICANT

DESCRIPTION

NEUTRAL LUBRICANT is a product specially formulated to facilitate the assembly of pipes with elastic joint. Due to its formulation with olein it does not affect any type of material.

PROPERTIES

Colour: Orange Smell: Soft Aspect: Pasty Viscosity: N.A/N.A Density: 0,91g/cm³

PH: 7.8

Non-flammable

Toxicity: Innocuous product

INSTRUCTIONS

It is applied directly on any elastic joint, either with a brush or by hand. The surface must have been previously cleaned. It does not need any type of treatment previous to the application.

PRESENTATION

Plastic tin 1Kg 12 units/box Plastic tin 5Kg 1 unit/ box

STORAGE

Duration: 12 months. Keep in fresh and dry place.

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.