

TECHNICAL DATA SHEET MULTI PURPOSE SILICONE

DESCRIPTION

Sealer with silicone rubber of acid reticulation, with anti-mould fungicides. One component system, of easy application and reticulation at room temperature. In contact with humidity air it becomes a rubber with excellent mechanical properties and resistant to the outdoor conditions. Also, resistant to blackening.

PROPERTIES

Colour: white/translucid
OLOUR: Acetic
Density: 0,93 gr/cm³
Descomposition temperature : N.A/N.A

APPLICATIONS

Sealing of bathtubs, washbasins, etc.
Sealing of shower screens. Used generally when a sealing has to undergo humidities with mild temperatures.

NOTE: Due to its acid reticulation, it must not be applied on the following materials.

- Building materials as concrete, masonry, not polished marble and similar.
- Ferrous metals, copper and brass. Rubbers, since a colouring of the sealant may be caused.

INSTRUCTIONS

The surfaces to be sealed must be clean and dry. If necessary, apart from a mechanical treatment it is convenient to carry out a cleaning with a non-greasy solvent, as for example acetone. As far as adherence is concerned, any material unknown by the user should be previously tested.

PRESENTATION

Plastic cartridges of 280 ml. 25 units/ box

STORAGE

Keep in fresh and dry place. Duration: 12 months.

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.