

TECHNICAL DATA SHEET ACRYLIC PUTTY

DESCRIPTION

Acrylic putty sealant is an elastic plastid top quality single component acrylic and adequate basis for interior and exterior applications. It can be painted.

PROPERTIES

Base: Acrylic resins
Density: 1-65-1.71 g/cm³
Hardness Shore A: Aprox. 30
Loss of tack: <25 min. Aprox. (1)
Elongation at break: 200 %
Vel. vulcanization: 1mm / 24 h (1)
Glide: <2 mm.
(1) Depending on the humidity and temperature

INSTRUCTIONS

ACRYLIC PUTTY is formulated for sealing construction joints with medium movement. It can be applied between windows and joints work together and carpentry work, in different interior work, repairing walls and paintable ceilings, walls prefabricated boards, etc.

It should not be used for expansion joints. For these applications we recommend silicone sealed. All surfaces should be clean, free of dust and grease. It is recommended that adhesion assay to determine the validity of the product for the required application. Cut the nozzle to the extent required thickness cord. Working between + 5 ° and + 40 ° C.

PRESENTATION

Cartridges of 300ml 25 units/box

STORAGE

Keep in fresh and dry place. Duration: 12 months.

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.