

TECHNICAL DATA SHEET ANTIHUMIDITY

DESCRIPTION

It has the particularity to absorb the humidity inserted in the installation surface that may be made of concrete paving flag or of another nature, drying it in less than 30 minutes, preparing it for a better adherence of the product to receive. It belongs to the system of waterproofing of any type of acrylic coating used in the elimination of humidities in terraces, covered, façades, etc. As a bridge of union and anchorage of the system to use.

INSTRUCTIONS

Stir the product thoroughly until it achieves its complete homogenization. Apply directly to the clean installation surface with a wool roller, with a consumption of 0,500 Kg/ml. It is ideal for the elimination of efflorescence's on plaster in bathrooms resulting from the condensation of water vapour. For other applications consult with our technical service.

OBSERVATIONS

As it is a flammable product, take the necessary precautions. Ventilate the places of application. Homogenize (stir up) before its use. Use protective mask in semi-closed places.

PRESENTATION

Tins of 25 Kg. Colour: white
Shelf life 12 months.

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.