

TECHNICAL DATA SHEET WATERPROOFING FAÇADES

High quality impermeable acrylic coating.

DEFINITION

It is a fluid paste with a good level of TIXOTROPY, of easy application by roller. Watery emulsion. It contains pigments of high resistance to UV.

APPLICATIONS

It can be applied in new work or repair. Before using WATERPROOFING FAÇADES in degraded or humid surfaces, it is recommended to apply first a coat of ANTIHUMIDITY (Priming), in order to prepare the installation surface and to neutralize the alkalinity.

PROPERTIES

Once applied and dried it has fungicidal properties. It is self washable, transpirable to water vapour, resistant to the outdoor conditions and totally waterproof.

INSTRUCTIONS

Clean and degrease the surfaces before its use, removing previously the loose elements that there could exist. Do not apply at temperatures below -5°C, with rain or unstable weather.

APPLICATION AND CONSUMPTION

The application can be carried out by wool roller, foam, brush or AIRLES equipment or similar. We recommend a minimum of 1 Kg/m² in several coats inserting POLIESTER MESH among them.

PRESENTATION

Tins of 25 Kg

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.