

## TECHNICAL DATA SHEET WATERPROOFING FAÇADES

High quality impermeable acrylic coating.

### DEFINITION

It is a fluid paste with a good level of TIXOTROPY, of easy application by roller. Watery emulsion. It contains pigments of high resistance to UV.

### APPLICATIONS

It can be applied in new work or repair. Before using WATERPROOFING FAÇADES in degraded or humid surfaces, it is recommended to apply first a coat of ANTIHUMIDITY (Priming), in order to prepare the installation surface and to neutralize the alkalinity.

### PROPERTIES

Once applied and dried it has fungicidal properties. It is self washable, transpirable to water vapour, resistant to the outdoor conditions and totally waterproof.

### INSTRUCTIONS

Clean and degrease the surfaces before its use, remaking previously the loose elements that there could exist. Do not apply at temperatures below -5°C, with rain or unstable weather.

### APPLICATION AND CONSUMPTION

The application can be carried out by wool roller, foam, brush or AIRLES equipment or similar. We recommend a minimum of 1 Kg/m<sup>2</sup> in several coats inserting POLIESTER MESH among them.

### PRESENTATION

Tins of 25 Kg

### RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

### NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.