

## TECHNICAL DATA SHEET WATER-REPELLENT

### DEFINITION

TENSE-ACTIVE preparation in aqueous base, colourless and one component liquid, applicable on absorbent prefabricated materials and of fibre concrete.

Rigorously waterproof. It allows perspiration and the evacuation of the inserted water vapour in the interior, it prevents efflorescences and does not alter the texture nor the colour of the installation surface (INVISIBLE). Once cured it is self washable.

### APPLICATIONS

This product can be applied by brush, roller, airless pistol or similar, and even with a simple sulphating machine.

Before application fissures must be sealed with conventional mortar or sealant.

At least 2 layers for a correct treatment needed. The second layer should be applied before drying the first one.

### CONSUMPTION

It will be always based on the porosity of the installation surface. (apply until saturation).

### OTHERS

The water-repellent is sensitive to freezes. Do not use it at temperatures below 5°C. Not flammable.

### PRESENTATION

Tin 5 Lts – Tin 25 Lts

Shelf life 12 months.

### RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

### NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.