

St. Esqueis, 25 - Pol. Ind. Can Sparin

C/. Esqueis, 25 - Pol. Ind. Can Barri 08415 Bigues (Barcelona) - Spain Tel: +34 93 865 68 28 Fax: +34 93 865 89 26 info@it3sa.com · www.it3sa.com

TECHNICAL DATA SHEET SEALING TAPE

DESCRIPTION

Seal tape of Polipropilene. Packing adhesive tape.

MAIN CHARACTERISTIC

Colour: Transparent / Brown

	<u>MESURE</u>	MIN	<u>MAX</u>	
Support thickness(µm):	28,0	26,6	29,4	UBIS E-05
Weight of adhesion (g/m ²):	17,0	15,0	19,0	UBIS E-05
Total Thickness (µm):	45,0	41,6	48,4	UBIS E-05
Elongation (%):	102	60	145	UBIS E-11
Tensile Strength (N/cm):	42,5	30,0	55,0	UBIS E-11
Adhesion:	1,8	1,3	2,3	UBIS E-01

PRESENTATION

Roll PP 66 meters. x 50 mm 36 unit/box Roll PP 132 meters x 50 mm 36 unit/box

RECOMMENDATIONS OF MANAGEMENT RESIDUES

Recommending for reason at the content of recipient, to deliver this recipient at a management residues person authorized for its destruction or its recuperation, as well as anything element to throw out that it was with contact with this product.

NOTE

The information supplied in this Specification Sheet is of general type following our experience. We cannot take responsibility by an inadequate use of the product.